

1 SP 5A-6



: 05002B06

, EN 1.4301 (AISI 304),

MS4020.55

40 °C.

Pt1000.
(DOL).

Maximum liquid temperature: 40 °C
 . t 0,15 / : 40 °C
 : 998.2 / ³ : 20 °C

: 2900 /

: 5 ³/₂₅
 : LIPSEAL
 : CE,EAC
 - : ISO9906:2012 3B
 : T40
 : SPLINE


EN 1.4301
 AISI AISI 304

EN 1.4301
 AISI AISI 304





DIN W.-Nr. 1.4301
 AISI 304

Rp1 1/2
 4 inch
 MS402
 CSIR
 - P2: 0.55
 (2), : 0.55
 50 Hz
 1 x 230
 5.8 A
 390 %
 Cos - : 0.74
 2860 /
 (IEC 34-5): IP68
 (IEC 85): B
 79213103
 MEI : 0.50
 ErP : EuP /
 11.4
 12.7
 10.8 ³
 C : DK
 8413702900

05002B06 SP 5A-6 50




	SP 5A-6
	05002B06
EAN	5700391118609
	2900 /
	5 ^{3/}
	25
	6
	NONE
	LIPSEAL
	CE,EAC
	ISO9906:2012 3B
	A
	YES
	T40
	SPLINE
	EN 1.4301
	AISI AISI 304
	EN 1.4301
	AISI AISI 304
	DIN W.-Nr. 1.4301
	AISI 304
	Rp1 1/2
	4 inch
Maximum liquid temperature:	40 °C
. t 0,15 /	40 °C
	20 °C
	998.2 / ³
	MS402
	CSIR
	GRUNDFOS
- P2:	0.55
(2),	0.55
	50 Hz
	1 x 230
	5.8 A
	390 %
Cos	0.74
	2860 /
(IEC 34-5):	IP68
(IEC 85):	B
	CONTACT
	79213103



:	
MEI :	0.50
ErP :	EuP / .
:	11.4
:	12.7
:	10.8 ³
C :	DK
:	8413702900

05002B06 SP 5A-6 50



05002B06 SP 5A-6 50

